



Creator Series C1S

British High-Fidelity Architectural Sound Redefined

This small Tier 1 in-ceiling loudspeaker is a two-way model featuring a C-CAM mid-bass driver and C-CAM tweeter. It has a cut-out dimension of 171 mm, revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitment.

Model	C1S
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.6 Ohm @ 150 Hz
Sensitivity (2.83Vrms @ 1m, Installed)	84 dB
Frequency Response, Installed (-6dB)	40 Hz – 30 kHz
Crossover Frequency	LF/HF: 3 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	110 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	50 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	25 – 100 W
Drive Unit Complement	1 x 5" (127 mm) C-CAM mid-bass driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	1.4 kg (3 lb 1 oz)
Mounting Depth	99 mm (3 7/8")
Cut-Out Hole Diameter	171 mm (6 3/4")
External Dimensions (Including Grille (H x W x D))	201 x 201 x 103 mm (7 15/16 x 7 15/16 x 4 4/16")
Cabinet Finish	Matte Black & Orange

