



Creator Series C2S

British High-Fidelity Architectural Sound Redefined

This small Tier 2 in-ceiling loudspeaker is a two-way model featuring an RST II mid-bass driver and C-CAM tweeter. It has a cut out dimension of 171 mm and revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	C2S
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.8 Ohm @ 150 Hz
Sensitivity (2.83Vrms @ 1m, Installed)	84 dB
Frequency Response, Installed (-6dB)	40 Hz – 30 kHz
Crossover Frequency	LF/HF: 2.5 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	111 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	65 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	35 – 130 W
Drive Unit Complement	1 x 5" (127 mm) RST II mid-bass driver 1 x 1 (25 mm) C-CAM tweeter
Weight (each)	1.5 kg (3 lb 5 oz)
Mounting Depth	99 mm (3 ⁷ / ₈ "
Cut-Out Hole Diameter	171 mm (6 ³ / ₄ "
External Dimensions (Including Grille (H x W x D))	201 x 201 x 103 mm (7 ¹⁵ / ₁₆ x 7 ¹⁵ / ₁₆ x 4 ⁴ / ₁₆ "
Cabinet Finish	Matte Black & Orange & Bronze

