



Creator Series C2M

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 2 in-ceiling loudspeaker is designed to deliver pristine, engaging acoustics where high-performance sound is a key requirement. It is a two-way model featuring an RST II mid-bass driver and C-CAM tweeter.

Model	C2M
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.6 Ohm @ 150 Hz
Sensitivity (2.83Vrms@1m, Installed)	86 dB
Frequency Response, Installed (-6dB)	35 Hz – 35 kHz
Crossover Frequency	LF/HF: 2.25 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	114 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	75 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	40 – 150 W
Drive Unit Complement	1 x 7" (178 mm) RST II mid-bass driver 1 x 1" x (25 mm) C-CAM tweeter
Weight (each)	2 kg (4 lb 6 oz)
Mounting Depth	99 mm (3 ⁷ / ₈ "
Cut-Out Hole Diameter	212 mm (8 ³ / ₈ "
External Dimensions (Including Grille (H x W x D))	242 x 242 x 103 mm (9 ¹ / ₂ x 9 ¹ / ₂ x 4 ¹ / ₁₆ "
Cabinet Finish	Matte Black & Orange & Bronze

