



Creator Series C2L

British High-Fidelity Architectural Sound Redefined

This large Tier 2 in-ceiling loudspeaker features an RST II mid-bass driver and C-CAM tweeter. It has a cut-out dimension of 248 mm and revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	C2L
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.4 Ohm @ 15 kHz
Sensitivity (2.83Vrms @ 1m, Installed)	88 dB
Frequency Response, Installed (-6dB)	30 Hz – 25 kHz
Crossover Frequency	LF/HF: 2 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	117 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	120 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	60 – 240 W
Drive Unit Complement	1 x 9" (229 mm) RST II bass driver 1 x 1.25" (32 mm) C-CAM tweeter
Weight (each)	2.5 kg (5 lb 8 oz)
Mounting Depth	99 mm (3 7/8")
Cut-Out Hole Diameter	248 mm (9 3/4")
External Dimensions (Including Grille (H x W x D))	278 x 278 x 103 mm (10 15/16 x 10 15/16 x 4 1/16")
Cabinet Finish	Matte Black & Orange & Bronze

