



Creator Series C3L-A

British High-Fidelity Architectural Sound Redefined

This large Tier 3 in-ceiling loudspeaker is a three-way model with an angled IDC II driver array that focuses sound mid-range and high-frequency sound into the listening area for improved clarity. Revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation.

Model	C3L-A
System Format	3-Way
Nominal Impedance	6 Ohm
Minimum Impedance (20Hz to 20kHz)	4.6 Ohm @ 2 kHz
Sensitivity (2.83Vrms @ 1m, Installed)	89 dB
Frequency Response, Installed (-6dB)	45 Hz – 35 kHz
Crossover Frequency	LF/MF: 700 Hz MF/HF: 3 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	119 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	150 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	60 – 225 W
Drive Unit Complement	1 x 9" (229 mm) RDT III bass driver 1 x 4" (102 mm) IDC II midrange driver 1 x 1" (25 mm) IDC II tweeter
Weight (each)	5.6 kg (12 lb 5 oz)
Mounting Depth	157 mm (6 3/16")
Cut-Out Hole Diameter	248 mm (9 3/4")
External Dimensions (Including Grille (H x W x D))	278 x 278 x 161 mm (10 15/16 x 10 15/16 x 6 5/16")
Cabinet Finish	Matte Black & Orange & Green

