



Creator Series C2L-T2X

British High-Fidelity Architectural Sound Redefined

This large Tier 2 in-ceiling loudspeaker can be utilised as both a single stereo speaker for music or as a di-pole or bi-pole surround sound speaker for exhilarating movie sound. It uses the patented Quik-Link speaker cable connector, which revolutionises the ease and speed of speaker installation.

Model	C2L-T2X
System Format	2-Way
Channels	1 (Mono) 2 (Stereo)
Nominal Impedance	4 Ohm (Mono) 8 Ohm (Stereo)
Minimum Impedance (20Hz to 20kHz)	3.2 Ohm @ 15 kHz (Mono) 6.4 Ohm @ 15 kHz (Stereo)
Sensitivity (2.83Vrms @ 1m, Installed)	88 dB
Frequency Response, Installed (-6dB)	30 Hz – 30 kHz
Crossover Frequency	LF/HF: 2 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	117 dB (Mono)
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	240 W (Mono) 2 x 30 – 120 W (Stereo)
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	60 – 240 W (Mono) 2 x 60 – 240 W (Stereo)
Drive Unit Complement	1 x 9" (229 mm) RST II dual-coil bass driver 2 x 1.25" (32 mm) C-CAM tweeter
Weight (each)	2.7 kg (6 lb)
Mounting Depth	99 mm (3 7/8")
Cut-Out Hole Diameter	248 mm (9 3/4")
External Dimensions (Including Grille (H x W x D))	278 x 278 x 103 mm (10 15/16 x 10 15/16 x 4 1/16")
Cabinet Finish	Matte Black & Orange & Bronze

