



Creator Series C2L-CP

British High-Fidelity Architectural Sound Redefined

This large Tier 2 in-ceiling loudspeaker features an RST II mid-bass driver and C-CAM tweeter. Its fully sealed back box delivers consistency of performance, no matter where it is used. A revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	C2L-CP
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.6 Ohm @ 10 kHz
Sensitivity (2.83Vrms @ 1m, Installed)	89 dB
Frequency Response, Installed (-6dB)	75 Hz – 25 kHz
Crossover Frequency	LF/HF: 2.25 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	120 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	100 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	50 – 200 W
Drive Unit Complement	1 x 9" (229 mm) RST II bass driver 1 x 1.25" (32 mm) C-CAM tweeter
Weight (each)	3.3 kg (7 lb 5 oz)
Mounting Depth	177.5 mm (6 ⁶³ / ₆₄ "
Cut-Out Hole Diameter	248 mm
External Dimensions (Including Grille (H x W x D))	278 x 278 x 181 mm (10 ¹⁵ / ₁₆ x 10 ¹⁵ / ₁₆ x 7 ¹ / ₈ "
Cabinet Finish	Matte Black & Orange & Bronze

