



Creator Series C2M-CP

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 2 in-ceiling loudspeaker features an RST II mid-bass driver and C-CAM tweeter. Its fully sealed back box delivers consistency of performance, no matter where it is used. A revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	C2M-CP
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.4 Ohm @ 15 kHz
Sensitivity (2.83Vrms @ 1m, Installed)	87 dB
Frequency Response, Installed (-6dB)	70 Hz – 35 kHz
Crossover Frequency	LF/HF: 2.5 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	116 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	65 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	35 – 130 W
Drive Unit Complement	1 x 7" (178 mm) RST II mid-bass driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	2.6 kg (5 lb 11 oz)
Mounting Depth	177.5 mm (6 ³ / ₁₆ ")
Cut-Out Hole Diameter	212 mm (8 ³ / ₈ ")
External Dimensions (Including Grille (H x W x D))	242 x 242 x 181.5 mm (9 ¹ / ₂ x 9 ¹ / ₂ x 4 ⁴ / ₁₆ ")
Cabinet Finish	Matte Black & Orange & Bronze

