



Creator Series C3L-CP

British High-Fidelity Architectural Sound Redefined

This large Tier 3 in-ceiling loudspeaker is a three-way model featuring an RDT III bass driver, IDC II midrange driver and IDC II tweeter with UD Waveguide II. Revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation.

Model	C3L-CP
System Format	3-Way
Nominal Impedance	6 Ohm
Minimum Impedance (20Hz to 20kHz)	4.9 Ohm @ 2 kHz
Sensitivity (2.83Vrms @ 1m, Installed)	89 dB
Frequency Response, Installed (-6dB)	80 Hz – 35 kHz
Crossover Frequency	LF/MF: 700 Hz MF/HF: 3.5 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	122 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	120 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	45 – 180 W
Drive Unit Complement	1 x 9" (229 mm) RDT III bass driver 1 x 4" (102 mm) IDC II midrange driver 1 x 1" (25 mm) IDC II tweeter
Weight (each)	5.7 kg (12 lb 10 oz)
Mounting Depth	177.5 mm (6 63/64")
Cut-Out Hole Diameter	248 mm (9 3/4")
External Dimensions (Including Grille (H x W x D))	278 x 278 x 181 mm (10 15/16 x 10 15/16 x 7 1/8")
Cabinet Finish	Matte Black & Orange & Green

