



Creator Series W1M-E

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 1 in-wall loudspeaker is a two-way model featuring a C-CAM mid-bass driver and C-CAM tweeter. Revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	W1M-E
System Format	2-Way
Nominal Impedance	8 ohm
Minimum Impedance (20Hz to 20kHz)	6.5 Ohm @ 200 Hz (6.2 Ohm @ 20 kHz)
Sensitivity (2.83Vrms@1m, Installed)	84 dB
Frequency Response, Installed (-6dB)	40 Hz – 30 kHz
Crossover Frequency	LF/HF: 2.5 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	110 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	50 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	25 – 100 W
Drive Unit Complement	1 x 5" (127 mm) C-CAM mid-bass driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	2.6 kg (5 lb 11 oz)
Mounting Depth	85 mm (3 ^{3/8} ")
Cut-Out Hole (LxW)	527 x 198 mm (20 ^{3/4} x 7 ^{13/16} ")
External Dimensions (Including Grille (H x W x D))	560 x 231 x 90 mm (22 ^{1/16} x 9 ^{1/8} x 3 ^{9/16} ")
Cabinet Finish	Matte Black & Orange

