



Creator Series W1M

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 1 in-wall loudspeaker is a two-way model featuring two C-CAM mid-bass drivers and a C-CAM tweeter. Revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	W1M
System Format	2-Way
Nominal Impedance	6 Ohm
Minimum Impedance (20Hz to 20kHz)	4.8 Ohm @ 15 kHz
Sensitivity (2.83Vrms@1m, Installed)	87 dB
Frequency Response, Installed (-6dB)	40 Hz – 30 kHz
Crossover Frequency	LF/HF: 2.75 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	113 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	75 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	30 – 110 W
Drive Unit Complement	2 x 5" (127 mm) C-CAM mid-bass driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	3.4 kg (7 lb 8 oz)
Mounting Depth	85 mm (3 3/8")
Cut-Out (LxW)	527 x 198 mm (20 3/4 x 7 13/16")
External Dimensions (Including Grille (H x W x D))	560 x 231 x 90 mm (22 1/16 x 9 1/8 x 3 9/16")
Cabinet Finish	Matte Black & Orange

