



# Creator Series W2M

## British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 2 in-wall loudspeaker is a three-way model featuring two RST II bass drivers, an RST II mid-range driver and a C-CAM tweeter. Revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

|                                                                                          |                                                                                                             |
|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Model                                                                                    | W2M                                                                                                         |
| System Format                                                                            | 3-Way                                                                                                       |
| Nominal Impedance                                                                        | 6 Ohm                                                                                                       |
| Minimum Impedance (20Hz to 20kHz)                                                        | 4.8 Ohm @ 1 kHz<br>(4.1 Ohm @ 15 kHz)                                                                       |
| Sensitivity (2.83Vrms@1m, Installed)                                                     | 87 dB                                                                                                       |
| Frequency Response, Installed (-6dB)                                                     | 40 Hz – 35 kHz                                                                                              |
| Crossover Frequency                                                                      | LF/HF: 650 kHz<br>MF/HF: 3 kHz                                                                              |
| Maximum Peak SPL* (single speaker @ 1m Z-Weighted)                                       | 116 dB                                                                                                      |
| Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor) | 120 W                                                                                                       |
| Recommended Amplifier Power (RMS into 8 OHM, Music Signal)                               | 45 – 180 W                                                                                                  |
| Drive Unit Complement                                                                    | 2 x 5" (127 mm) RST II bass driver<br>1 x 3" (76 mm) RST II midrange driver<br>1 x 1" (25 mm) C-CAM tweeter |
| Weight (each)                                                                            | 3.9 kg (8 lb 9 oz)                                                                                          |
| Mounting Depth                                                                           | 85 mm (3 3/8")                                                                                              |
| Cut-Out (LxW)                                                                            | 527 x 198 mm (20 3/4 x 7 13/16")                                                                            |
| External Dimensions (Including Grille (H x W x D))                                       | 560 x 231 x 90 mm (22 1/16 x 9 1/8 x 3 9/16")                                                               |
| Cabinet Finish                                                                           | Matte Black & Orange & Bronze                                                                               |

