



Creator Series W2M-CP

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 2 in-wall loudspeaker is a three-way model featuring two RST II bass drivers, an RST II mid-range driver and a C-CAM tweeter. Its fully sealed back box delivers consistency of performance, no matter where it is used. A revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	W2M-CP
System Format	3-Way
Nominal Impedance	6 Ohm
Minimum Impedance (20Hz to 20kHz)	4.8 Ohm @ 1 kHz (4.3 Ohm @ 15 kHz)
Sensitivity (2.83Vrms@1m, Installed)	87 dB
Frequency Response, Installed (-6dB)	60 Hz – 35 kHz
Crossover Frequency	LF/HF: 550 kHz MF/HF: 3 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	118 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	100 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	40 – 150 W
Drive Unit Complement	2 x 5" (127 mm) RST II bass driver 1 x 3" (76 mm) RST II mid-range driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	4.4 kg (9 lb 11 oz)
Mounting Depth	97 mm (3 13/16")
Cut-Out (LxW)	527 x 198 mm (20 3/4 x 7 13/16")
External Dimensions (Including Grille (H x W x D))	560 x 231 x 102 mm (2 21/16 x 9 1/8 x 4 1/64")
Cabinet Finish	Matte Black & Orange & Bronze

