



Creator Series W3M

British High-Fidelity Architectural Sound Redefined

This high-performance, medium-sized Tier 3 in-wall loudspeaker is a three-way model featuring two RDT III bass drivers, a C-CAM mid-range driver and MPD II transducer.

Model	W3M
System Format	3-Way
Nominal Impedance	6 Ohm
Minimum Impedance (20Hz to 20kHz)	4.8 Ohm @ 150 Hz
Sensitivity (2.83Vrms@1m, Installed)	88 dB
Frequency Response, Installed (-6dB)	45 Hz – 60 kHz
Crossover Frequency	LF/HF: 650 kHz MF/HF: 3.5 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	122 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	150 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	60 – 225 W
Drive Unit Complement	2 x 5" (127 mm) RDT III bass driver 1 x 3" (76 mm) C-CAM midrange driver 1 x MPD II transducer
Weight (each)	4.7 kg (10 lb 6 oz)
Mounting Depth	85 mm (3 ³ / ₈ "
Cut-Out Hole (LxW)	527 x 198 mm (20 ³ / ₄ x 7 ¹³ / ₁₆ "
External Dimensions (Including Grille (H x W x D))	560 x 231 x 90 mm (22 ¹ / ₁₆ x 9 ¹ / ₈ x 3 ⁹ / ₁₆ "
Cabinet Finish	Matte Black & Orange

