



Creator Series C2M-T2X

British High-Fidelity Architectural Sound Redefined

This medium-sized Tier 2 in-ceiling loudspeaker can be utilised as both a single stereo speaker for music or as a di-pole or bi-pole surround sound speaker for exhilarating movie sound. It uses the patented Quik-Link speaker cable connector, which revolutionises the ease and speed of speaker installation.

Model	C2M-T2X
System Format	2-Way
Channels	1 (Mono) 2 (Stereo)
Nominal Impedance	4 Ohm (Mono) 8 Ohm (Stereo)
Minimum Impedance (20Hz to 20kHz)	3.4 Ohm @ 15 kHz (Mono) 6.8 Ohm @ 15 kHz (Stereo)
Sensitivity (2.83Vrms @ 1m, Installed)	86 dB
Frequency Response, Installed (-6dB)	35 Hz – 30 kHz
Crossover Frequency	LF/HF: 2.25 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	114 dB (Mono)
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	150 W (Mono) 2 x 75 W (Stereo)
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	40 – 150 W (Mono) 2 x 20 – 75 W (Stereo)
Drive Unit Complement	1 x 7" (178 mm) RST II dual-coil bass driver 2 x 1" (25 mm) C-CAM tweeter
Weight (each)	2.1 kg (4 lb 10 oz)
Mounting Depth	99 mm (3 7/8")
Cut-Out Hole Diameter	212 mm (8 3/8")
External Dimensions (Including Grille (H x W x D))	242 x 242 x 103 mm (9 1/2 x 9 1/2 x 4 1/16")
Cabinet Finish	Matte Black & Orange & Bronze

