



Creator Series C1M

British High-Fidelity Architectural Sound Redefined

This medium Tier 1 in-ceiling loudspeaker is a two-way model featuring a C-CAM mid-bass driver and C-CAM tweeter. It has a cut-out dimension of 212 mm, revolutionary patented Quik-Link speaker cable connector and Tri-Grip II for quick, simple, reliable and strong installation and fitting.

Model	C1M
System Format	2-Way
Nominal Impedance	8 Ohm
Minimum Impedance (20Hz to 20kHz)	6.5 Ohm @ 150 Hz
Sensitivity (2.83Vrms @ 1m, Installed)	86 dB
Frequency Response, Installed (-6dB)	35 Hz – 30 kHz
Crossover Frequency	LF/HF: 2 kHz
Maximum Peak SPL* (single speaker @ 1m Z-Weighted)	113 dB
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	65 W
Recommended Amplifier Power (RMS into 8 OHM, Music Signal)	35 – 130 W
Drive Unit Complement	1 x 7" (178 mm) C-CAM mid-bass driver 1 x 1" (25 mm) C-CAM tweeter
Weight (each)	1.9 kg (4 lb 3 oz)
Mounting Depth	99 mm (3 7/8")
Cut-Out Hole Diameter	212 mm (8 3/8")
External Dimensions (Including Grille (H x W x D))	242 x 242 x 103 mm (9 1/2 x 9 1/2 x 4 1/16")
Cabinet Finish	Matte Black & Orange

